

UKCA Certificate of Constancy of Performance

This is to certify that:

ISEO Serrature SpA
Via San Girolamo, 13
Pisogne
Brescia
25055
Italy

Holds Certificate Number:

0086 CPR 747904

In respect of:

BS EN 179:2008 - Emergency Exit Devices

Mod. 214, 212

Mod. Lever handles plus DINFIR3 locks

Mechanically operated by either a lever handle or a push pad for the purpose of achieving a safe exit under an emergency situation on escape routes.

In compliance with the Regulation (UK) Statutory Instrument 2019 No 465 of the United Kingdom Parliament (Construction Products (Amendment etc.) (EU Exit) Regulations or CPR), this certificate applies to the above construction product. This certificate attests that all the provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the above standard(s) under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product. This certificate was first issued on the date below and will remain valid as long as neither the designated standard, the construction product, the AVCP methods, nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the approved product certification body.

For and on behalf of BSI, an Approved Body for the above Regulation (Approved Body Number 0086):

Frank Lee, Product Certification Technical and Compliance Director

First Issued: 2021-07-14

Effective Date: 2022-03-07

Latest Issue: 2022-03-07

Page: 1 of 5

...making excellence a habit.™

UKCA Certificate of Constancy of Performance

No. 0086 CPR 747904

BS EN 179:2008 - Building hardware - Emergency exit devices operated by a lever handle or push pad, for use on escape routes.

Table 1: Requirements for emergency exit devices in line with BS EN 179:2008 (to be read in conjunction with Tables 2 and 3)			
Product:	Emergency exit devices operated by a lever handle or a push pad as covered by the scope of BS EN 179:2008.		
Intended use:	For doors on escape routes.		
Essential characteristics	Clauses within BS EN 179:2008	Compliance	
		Mod. 214, 212	Mod. Lever handles plus DINFIR3 locks
Ability to release (for doors on escape routes)	4.2.1	Achieved	Achieved
Durability of ability to release against aging and degradation (for doors on escape routes)	4.2.1	Achieved	Achieved
Self closing ability C (for fire/smoke doors on escape routes)	4.2.1	Achieved	Achieved
Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes)	4.2.1	Achieved	Achieved
Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)	4.2.1	Achieved	Achieved
Control of Dangerous substances	4.1.29	Achieved	Achieved
Note:	<i>This details only those essential characteristics as required in the ZA Annex of BS EN 179:2008 and applicable to lever handle or a push pad operation.</i>		

First Issued: 2021-07-14

Effective Date: 2022-03-07

Latest Issue: 2022-03-07

Page: 2 of 5

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 747904

BS EN 179:2008 - Building hardware - Emergency exit devices operated by a lever handle or push pad, for use on escape routes.

Table 2: Product Information – Emergency Exit Devices suitable for use on smoke door assemblies based on a test in accordance with EN 1634-1			
No	Description	Additional Information	Model
1	Emergency exit device	Emergency exit device operated by lever handle	Mod. 214, 212
Models		NORMBAU, MUSTER, VIELER ER.FSG.522, HEWI 230, ECO SCHULTE 1030 / 1035 / 0110 / 0115 / 0116, ECO SCHULTE 0330 / 0410 / 0415 / 0490, HOPPE PARIS (Lever Handles) 214***65** (Lock Active Leaf) 212***65* (Lock Inactive Leaf)	
Accessories		032094, 94100160, 032144*, 032714*, 032724*, 032744*, 032154*, 032174*, 032704*, 032164* 032184*, 0321A4*, ARIES OOE1***10**, 032532*, 03243**, 03241**, 032515*, 03246**, 03242**, 03240**, 03250**, 03245**	
Note		Emergency exit devices detailed in table 2 have conformed to the requirements of BS EN 179:2008, Table 1: Performance characteristics and compliance criteria.	

First Issued: 2021-07-14

Effective Date: 2022-03-07

Latest Issue: 2022-03-07

Page: 3 of 5

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 747904

BS EN 179:2008 - Building hardware - Emergency exit devices operated by a lever handle or push pad, for use on escape routes.

Table 3: Product Information – Emergency Exit Devices suitable for use on smoke door assemblies based on a test in accordance with EN 1634-1			
No	Description	Additional Information	Model
1	Emergency exit device	Emergency exit device operated by lever handle	Mod. Lever handles plus DINFIR3 locks
Models		NORMBAU, MUSTER, VIELER ER.FSG.522, HEWI 230, ECO SCHULTE 1030/1035/0110/0115/0116 ECO SCHULTE 0330 0410/0415/0490, HOPPE PARIS (lever handles) 2DB*, 2DC*, 2DD*, 2DE* (Lock active leaf) 2D7* (Lock inactive leaf)	
Accessories		03865*, 94100160, 032144*, 032714*, 032724*, 032744*, 032154*, 032174*, 032704*, 032164*, 032314*, 032184*, 0321A4*, ARIES OOE1***10**, 032532*, 03243**, 03241**, 032515*, 03246**, 03242**, 03240**, 03250**, 03245**	
Note		Emergency exit devices detailed in table 3 have conformed to the requirements of BS EN 179:2008, Table 1: Performance characteristics and compliance criteria.	

First Issued: 2021-07-14

Effective Date: 2022-03-07

Latest Issue: 2022-03-07

Page: 4 of 5

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

UKCA Certificate of Constancy of Performance

No. 0086 CPR 747904

Manufacturing Plant	Series	Certified Activities
E01	Mod. 214, 212 Mod. Lever handles plus DINFIR3 locks	BS EN 179:2008 – Building hardware – Emergency exit devices operated by a lever handle or push pad, for use on escape routes.
E41	Mod. 214, 212 Mod. Lever handles plus DINFIR3 locks	BS EN 179:2008 – Building hardware – Emergency exit devices operated by a lever handle or push pad, for use on escape routes.

First Issued: 2021-07-14

Latest Issue: 2022-03-07

Effective Date: 2022-03-07

Page: 5 of 5

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.