

741N

**MORTICE LOCKS,
CENTRE DISTANCE 85**



PRODUCT

The mortice lock **741N** series with **centre distance 85**, with new features and a wider range, can be installed on metal doors or wooden frame doors with glass. It can be used with the wide range of Iseo cylinders, giving to the doors different security levels.

OPERATION

The deadbolt and the latchbolt are operated by the key.
The latchbolt is operated by the handle.

RANGE

Mechanical lateral locks, centre distance 85, with the following functions:

- Latchbolt and deadbolt (741N series - 200N series);
- Roller and deadbolt (743N series);
- Deadbolt only (745N series);
- Latchbolt only (749N series).

CERTIFICATION

EN12209

COMPATIBLE PRODUCTS

- Striking plates (please refer to ISEO general catalogue).

TEXT FOR SPECIFICATIONS:

ISEO 741N series mortice locks for framed glass doors, with 85 mm handle-cylinder centre distance, latch retractable with handle and key, and 14 mm thick latch with 10.3 mm protrusion.

ISEO®

TECHNICAL FEATURES:

- 85 mm centre distance**
with european profile cylinders
- Latchbolt operated by handle and key**
- Latchbolt and deadbolt flush with front plate**
- 8 mm handle follower**
- 741N series is interchangeable with the previous version 741**
- For metal frames (codes 741N):**
 - Backsets 20, 25, 30, 35 mm (real backsets 21, 26, 31, 36 mm)
 - 22 mm squared front plate
 - Front plate in chrome-plated steel (2,7 mm thickness) or in stainless steel (3 mm thickness)
- For wooden frames (codes 200N):**
 - Backsets 25, 30, 35 mm (real backsets 26, 31, 36 mm)
 - Front plate in brass-plated steel or in gold-painted steel (2,7 mm thickness)

KEY POINT

- Closed case on all sides. This stops door chips and shavings from getting jammed in the lock;
- 2 fixing holes, 21,5 mm (bottom) and 46 mm (top) from the handle;
- Case painted marbled grey;
- Reversible latchbolt, no tools necessary;
- 15 mm single throw.

www.iseo.com