Smart Gateway

WIFI

Version WiFi

IT ALLOWS YOU TO MANAGE YOUR ARGO SYSTEM FROM REMOTE WITHOUT CABLED IP CONNECTIONS





Control the system remotely

With Smart Gateway, the ARGO system by ISEO can be controlled remotely, in residential but also in 'light' commercial environments, such as shops, small offices, B&Bs, where the new smart devices generation for door locks it can simplify your daily life and make logistics easier.


Connection security

The ARGO 3.0 system guarantees a secure connection thanks to Bluetooth Smart 5.0 and end-to-end encryption, which manages communication without an intermediate server.

Product features

- "Desktop" format with the possibility of wall mounting
- Data conversion (WIFI or Ethernet) to Bluetooth®

Smart Gateway WIFI



DIMENSIONS
- Width: 125 mm
- Depth: 40 mm
- Height: 85 mm

MATERIAL
Technopolymer

COLOUR
White

cod. **5E075524**

COMMUNICATION INTERFACE

- Conversion from WIFI data to Bluetooth®
- Dual Band WIFI at 2.4 GHz and 5 GHz
- USB type C

Technical features

FIRMWARE
ARGO

POWER UNIT
Powered by USB C +5VDC input power 2A (10W). Power supply not included (accessory to order separately).

HARDWARE SPECIFICATIONS
ARM A7 based CPU module
512 MB RAM
8 GB Flash eMMC Non volatile Memory

OPERATING SYSTEM
Embedded Linux

MOUNTING

- Desktop
- Wall mounted

WORKING TEMPERATURE
0°C ÷ +50°C

STORAGE TEMPERATURE
-25°C ÷ +75°C

PACKAGE
1 Smart Gateway WIFI Power supply not included (accessory to order)

ACCESSORIES (NOT INCLUDED)
Power supply (cod. 0000A00155)
Wall fixing brackets kit (cod. 0000A00154)

Compatibility with ISEO applications

ARGO	LUCKEY	LSA	V364
•	-	-	-