

# Smart Gateway



## WIFI

### Version WiFi

IT ALLOWS YOU TO MANAGE YOUR ARGO SYSTEM FROM REMOTE WITHOUT CABLED IP CONNECTIONS



### Control the system remotely



With Smart Gateway, the ARGO system by ISEO can be controlled remotely, in residential but also in 'light' commercial environments, such as shops, small offices, B&Bs, where the new smart devices generation for door locks it can simplify your daily life and make logistics easier.

### Connection security

The ARGO 3.0 system guarantees a secure connection thanks to Bluetooth Smart 5.0 and end-to-end encryption, which manages communication without an intermediate server.

### Product features

- "Desktop" format with the possibility of wall mounting
- Data conversion (WIFI or Ethernet) to Bluetooth®

**DIMENSIONS**

- Width: 125 mm
- Depth: 40 mm
- Height: 85 mm

**MATERIAL**

 Technopolymer

**COLOUR**

 White

cod. **5E075524**

**COMMUNICATION INTERFACE**

- Conversion from WIFI data to Bluetooth®
- Dual Band WIFI at 2.4 GHz and 5 GHz
- USB type C

## Technical features

**FIRMWARE**

ARGO

- Desktop
- Wall mounted

**POWER UNIT**

Powered by USB C +5VDC input power 2A (10W). Power supply not included (accessory to order separately).

**WORKING TEMPERATURE**

0°C ÷ +50°C

**HARDWARE SPECIFICATIONS**

ARM A7 based CPU module  
512 MB RAM  
8 GB Flash eMMC Non volatile Memory

**STORAGE TEMPERATURE**

-25°C ÷ +75°C

**PACKAGE**

1 Smart Gateway WIFI Power supply not included (accessory to order)

**OPERATING SYSTEM**

Embedded Linux

**ACCESSORIES (NOT INCLUDED)**

Power supply (cod. 0000A00155)  
Wall fixing brackets kit (cod. 0000A00154)

**MOUNTING**

## Compatibility with ISEO applications

| ARGO                                                                                | LUCKY | LSA | V364 |
|-------------------------------------------------------------------------------------|-------|-----|------|
|  | -     | -   | -    |